



## SAFETY DATA SHEET

Page 1 of 2

### ANTI-STATIC CLEANER FOR PLASTICS

Revision 0  
Revision date 13-Oct-2006

#### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

**Product name** ANTI-STATIC CLEANER FOR PLASTICS  
**Company** Pro-Spray Automotive Finishes Ltd  
Whitehall Industrial Estate  
Cambridge Road  
Croxton  
St Neots  
PE19 6SS  
Catherine@pro-spray.co.uk  
**Telephone** +44 (0) 1480 880035  
**Fax** +44 (0) 1480 880108  
**Product code** ICR-1050

#### 2. COMPOSITION / INFORMATION ON INGREDIENTS

##### Hazardous ingredients

|  | Conc.  | CAS        | EINECS    | Symbols/Risk phrases                |
|--|--------|------------|-----------|-------------------------------------|
| 1,3,5-Trimethylbenzene   | 1-10%  | 108-67-8   | 203-604-4 | R10 Xi; R37 N; R51/53               |
| Cumene   | 1-10%  | 98-82-8    | 202-704-5 | R10 Xn; R65 Xi; R37 N; R51/53       |
| 1,2,4-Trimethylbenzene   | 20-30% | 95-63-6    | 202-436-9 | R10 Xn; R20 Xi; R36/37/38 N; R51/53 |
| Low boiling point naphtha - unspecified - solvent<br>naphtha (petroleum), light arom | 40-50% | 64742-95-6 | 265-199-0 | Xi; R37-66 N; R51/53 R10-67         |
| n-Propanol<br>(Propan-1-ol)  | 20-30% | 71-23-8    | 200-746-9 | F; R11 Xi; R41 R67                  |

#### 3. HAZARDS IDENTIFICATION

**Main hazards** Irritating to respiratory system and skin. Risk of serious damage to eyes. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

#### 4. FIRST AID MEASURES

#### 5. FIRE FIGHTING MEASURES

#### 6. ACCIDENTAL RELEASE MEASURES

#### 7. HANDLING AND STORAGE

Print date

10-Aug-2007

# ANTI-STATIC CLEANER FOR PLASTICS

Revision 0  
Revision date 13-Oct-2006

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure limits

|                             |  |  |
|-----------------------------|--|--|
| Cumene                      | WEL 8-hr limit ppm: 25<br>WEL 15 min limit ppm: 50   | WEL 8-hr limit mg/m3: 125<br>WEL 15 min limit mg/m3: 250 |
| n-Propanol<br>(Propan-1-ol) | WEL 8-hr limit ppm: 200<br>WEL 15 min limit ppm: 250 | WEL 8-hr limit mg/m3: 500<br>WEL 15 min limit mg/m3: 625 |

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## 10. STABILITY AND REACTIVITY

## 11. TOXICOLOGICAL INFORMATION

## 12. ECOLOGICAL INFORMATION

## 13. DISPOSAL CONSIDERATIONS

## 14. TRANSPORT INFORMATION

## 15. REGULATORY INFORMATION

|                       |  |
|-----------------------|--|
| <b>Risk phrases</b>   | R37/38 - Irritating to respiratory system and skin.<br>R41 - Risk of serious damage to eyes.<br>R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.<br>R66 - Repeated exposure may cause skin dryness or cracking.<br>R67 - Vapours may cause drowsiness and dizziness. |
| <b>Safety phrases</b> | S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.<br>S29 - Do not empty into drains.<br>S39 - Wear eye/face protection.  |

## 16. OTHER INFORMATION

|  |   |
|--|---|
| <b>Text of risk phrases in Section 2</b> | R10 - Flammable.<br>R11 - Highly flammable.<br>R20 - Harmful by inhalation.<br>R36/37/38 - Irritating to eyes, respiratory system and skin.<br>R37 - Irritating to respiratory system.<br>R41 - Risk of serious damage to eyes.<br>R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.<br>R65 - Harmful: may cause lung damage if swallowed.<br>R66 - Repeated exposure may cause skin dryness or cracking.<br>R67 - Vapours may cause drowsiness and dizziness. |
|--|---|