



SAFETY DATA SHEET

Page 1 of 4

intermix red oxide tinter

Revision 0
Revision date 13-Oct-2006

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name intermix red oxide tinter

Company Pro-Spray Automotive Finishes Ltd
Whitehall Industrial Estate
Cambridge Road
Croxtan
St Neots
PE19 6SS
Catherine@pro-spray.co.uk

Telephone +44 (0) 1480 880035

Fax +44 (0) 1480 880108

Product code mb-206

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

| | Conc. | CAS | EINECS | Symbols/Risk phrases |
|---|--------|-----------|-----------|------------------------|
| n-Butyl acetate (Butyl acetate) | 20-30% | 123-86-4 | 204-658-1 | R10 R66 R67 |
| Ethylbenzene | 1-10% | 100-41-4 | 202-849-4 | F; R11 Xn; R20 |
| Xylene (Xylene, o-, m-, p- or mixed isomers) | 10-20% | 1330-20-7 | 215-535-7 | R10 Xn; R20/21 Xi; R38 |
| 2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate) | 0-0.5% | 108-65-6 | 203-603-9 | R10 Xi; R36 |
| C.I. Pigment Red 101 (Rouge respirable) | 10-20% | 1309-37-1 | 215-168-2 | |

3. HAZARDS IDENTIFICATION

Main hazards Vapours may cause drowsiness and dizziness. Flammable Harmful by inhalation and in contact with skin. Repeated exposure may cause skin dryness or cracking.

4. FIRST AID MEASURES

Skin contact May cause irritation to skin. Wash off immediately with plenty of soap and water.
Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye contact May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.

Ingestion Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist.

General information In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

intermix red oxide tint

Revision 0
Revision date 13-Oct-2006

5. FIRE FIGHTING MEASURES

| | |
|-----------------------------|--|
| Extinguishing media | Alcohol resistant foam. Carbon dioxide (CO2) Dry chemical. Do NOT use water jet. |
| Fire hazards | Burning produces irritating, toxic and obnoxious fumes. Fire will produce dense black smoke. |
| Protective equipment | Self-contained breathing apparatus. |

6. ACCIDENTAL RELEASE MEASURES

| | |
|----------------------------------|--|
| Personal precautions | Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Eliminate all sources of ignition. Wear suitable protective equipment. |
| Environmental precautions | Do not allow product to enter drains. Prevent further spillage if safe. |
| Clean up methods | Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water. |

7. HANDLING AND STORAGE

| | |
|-----------------|--|
| Handling | Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. |
| Storage | Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

| | | |
|---|--|--|
| n-Butyl acetate (Butyl acetate) | WEL 8-hr limit ppm: 150 WEL 15 min limit ppm: 200 | WEL 8-hr limit mg/m3: 724 WEL 15 min limit mg/m3: 966 |
| Ethylbenzene | WEL 8-hr limit ppm: 100 WEL 15 min limit ppm: 125 | WEL 8-hr limit mg/m3: 441 WEL 15 min limit mg/m3: 552 |
| Xylene (Xylene, o-,m-,p-or mixed isomers) | WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100 | WEL 8-hr limit mg/m3: 220 WEL 15 min limit mg/m3: 441 |
| 2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate) | WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100 | WEL 8-hr limit mg/m3: 274 WEL 15 min limit mg/m3: 548 |
| C.I. Pigment Red 101 (Rouge respirable) | WEL 8-hr limit ppm: - WEL 15 min limit ppm: - | WEL 8-hr limit mg/m3: 4 WEL 15 min limit mg/m3: - |
| C.I. Pigment Red 101 (Rouge total inhalable) | WEL 8-hr limit ppm: - WEL 15 min limit ppm: - | WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3: - |
| C.I. Pigment Red 101 (Iron oxide, fume (as Fe)) | WEL 8-hr limit ppm: - WEL 15 min limit ppm: - | WEL 8-hr limit mg/m3: 5 WEL 15 min limit mg/m3: 10 |

| | |
|-------------------------------|---|
| Engineering measures | Ensure adequate ventilation of the working area. |
| Respiratory protection | Wear suitable respiratory equipment when necessary. |
| Hand protection | Chemical resistant gloves (PVC) |
| Eye protection | Approved safety goggles. |
| Protective equipment | Wear chemical protective clothing. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-------------------------|----------------------|
| Description | Liquid. |
| Flash point | 21°C |
| Water solubility | immiscible in water. |

intermix red oxide tinter

Revision 0
Revision date 13-Oct-2006

10. STABILITY AND REACTIVITY

| | |
|---|---|
| Stability | Stable under normal conditions. |
| Conditions to avoid | Heat, sparks and open flames. |
| Materials to avoid | Oxidising agents. Acids. Alkaline solution. |
| Hazardous decomposition products | Carbon oxides. Nitrogen oxides. |

11. TOXICOLOGICAL INFORMATION

| | |
|---------------------------------------|--|
| Acute toxicity | No data is available on this product. Exposure above the recommended occupational exposure limit (OEL) may cause adverse health effects. Inhalation is irritating to the respiratory tract and may cause damage to the central nervous system. |
| Corrosivity | May cause irritation to eyes and respiratory system. |
| Repeated or prolonged exposure | May cause dermatitis. |

12. ECOLOGICAL INFORMATION

| | |
|--------------------|---------------------------------------|
| Ecotoxicity | No data is available on this product. |
|--------------------|---------------------------------------|

13. DISPOSAL CONSIDERATIONS

| | |
|------------------------------|--|
| General information | Dispose of in compliance with all local and national regulations. |
| Disposal of packaging | Containers must be recycled in compliance with national legislation and environmental regulations. |

14. TRANSPORT INFORMATION

ADR/RID

| | |
|----------------------|-------------------|
| UN 1263 | Packing group III |
| Class 3 | Hazard ID 33 |
| Proper Shipping Name | |
| PAINT . | |

IMDG

| | |
|------------------|--------------------|
| UN 1263 | Packing group III |
| Class 3 | Marine pollutant . |
| EmS Code F-E S-E | |


IATA

| | |
|-------------------------------------|------------------------|
| UN 1263 | Packing group III |
| Class 3 | Subsidiary risk - |
| Packing Instruction 310 (Cargo) | Maximum quantity 220 L |
| Packing Instruction 309 (Passenger) | Maximum quantity 60 L |

intermix red oxide tinter

Revision 0
Revision date 13-Oct-2006

15. REGULATORY INFORMATION

| | |
|-----------------------|--|
| Labelling | The product is classified in accordance with 67/548/EEC. |
| Symbols | Xn - Harmful  |
| Risk phrases | R67 - Vapours may cause drowsiness and dizziness. R10 - Flammable. R20/21 - Harmful by inhalation and in contact with skin. R66 - Repeated exposure may cause skin dryness or cracking. |
| Safety phrases | S36/37 - Wear suitable protective clothing and gloves. |

16. OTHER INFORMATION

| | |
|--|--|
| Text of risk phrases in Section 2 | R10 - Flammable. R11 - Highly flammable. R20 - Harmful by inhalation. R20/21 - Harmful by inhalation and in contact with skin. R36 - Irritating to eyes. R38 - Irritating to skin. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness. |
| Further information | The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. |