Printing date 26.06.2008 Revision: 26.06.2008

I Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: ProXL - Pro2kPrime

· Article number: 227547

· Application of the substance / the preparation Priming

· Manufacturer/Supplier:

ProXL

Second Avenue

Chatham

Kent

ME4 5AU

Tel: +44(0)1634823900 Fax: +44(0)1634813807 Email: info@pro-xl.co.uk

· Further information obtainable from: QHSE Department

• Information in case of emergency: Tel: +44(0) 1634 823900 (08.00 / 17.00)

2 Hazards identification

· Hazard description:





Xi Irritant

F+ Extremely flammable

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

Has a narcotizing effect.

R 12 Extremely flammable.

R 36 Irritating to eyes.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- · Chemical characterization
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	ents:		
CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether	i F+; R 12	25-50%
CAS: 123-86-4 EINECS: 204-658-1		R 10-66-67	10-25%

(Contd. on page 2)

Printing date 26.06.2008 Revision: 26.06.2008

Trade name: ProXL - Pro2kPrime

		(Conto	d. of page 1)
CAS: 67-64-1 EINECS: 200-662-2	acetone	※ Xi, 🔥 F; R 11-36-66-67	10-25%
CAS: 78-83-1 EINECS: 201-148-0	butanol	Xi; R 10-37/38-41-67	≤ 2.5%
CAS: 1330-20-7 EINECS: 215-535-7	xylene	X Xn, X Xi; R 10-20/21-38	≤ 2.5%
CAS: 110-43-0 EINECS: 203-767-1	heptan-2-one	Xn; R 10-20/22	≤ 2.5%
CAS: 1314-13-2 EINECS: 215-222-5	zinc oxide	₹ N; R 50/53	≤ 2.5%

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

5 Fire-fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

· Protective equipment: No special measures required.

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Measures for cleaning/collecting:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

7 Handling and storage

- · Handling:
- · Information for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

· Information about storage in one common storage facility: Not required.

(Contd. on page 3)

Printing date 26.06.2008 Revision: 26.06.2008

Trade name: ProXL - Pro2kPrime

(Contd. of page 2)

· Further information about storage conditions:

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

78-83-1 butanol

WEL Short-term value: 231 mg/m³, 75 ppm Long-term value: 154 mg/m³, 50 ppm

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

110-43-0 heptan-2-one

WEL Short-term value: 475 mg/m³, 100 ppm Long-term value: 237 mg/m³, 50 ppm

Sk

· Additional information: The lists valid during the making were used as basis.

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection: Not required.

· Protection of hands:

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Natural rubber, NR

(Contd. on page 4)

Printing date 26.06.2008 Revision: 26.06.2008

Trade name: ProXL - Pro2kPrime

(Contd. of page 3)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Natural rubber, NR

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information

Form: Aerosol

Colour: According to product specification

Odour: Characteristic

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

 Lower:
 1.2 Vol %

 Upper:
 18.6 Vol %

 · Vapour pressure at 20°C:
 5200 hPa

• Density at $20^{\circ}C$: 1.06 g/cm³

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

VOC-EU 66.2 %

681.7 g/l / 5.69 lb/gl

VOC-(EU) 698.7 g/l

10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Acute toxicity:

· LD/LC50 values relevant for classification:

67-64-1 acetone

 Oral
 LD50
 5800 mg/kg (rat)

 Dermal
 LD50
 20000 mg/kg (rabbit)

(Contd. on page 5)

Printing date 26.06.2008 Revision: 26.06.2008

Trade name: ProXL - Pro2kPrime

(Contd. of page 4)

1314-13-2 zinc oxide

Oral LD50 7950 mg/kg (mouse)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

15 01 04 metallic packaging

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 2 5F Gases.

Danger code (Kemler): UN-Number: 1950
Packaging group: Hazard label 2.1

· Description of goods: 1950 AEROSOLS

· Limited quantities (LQ) LQ2

(Contd. on page 6)

Printing date 26.06.2008 Revision: 26.06.2008

Trade name: ProXL - Pro2kPrime

(Contd. of page 5)

· Maritime transport IMDG:



· IMDG Class: 2.1 · UN Number: 1950 · Label 2.1 · Packaging group:

Packaging group:
EMS Number:
Marine pollutant:
Proper shipping name:

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 2.1 · UN/ID Number: 1950 · Label 2.1 · Packaging group: -

· Proper shipping name: AEROSOLS, flammable

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:





Xi Irritant

F+ Extremely flammable

· Risk phrases:

- 12 Extremely flammable.
- 36 Irritating to eyes.
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 2 Keep out of the reach of children.
- 23 Do not breathe aerosol.
- 24/25 Avoid contact with skin and eyes.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

(Contd. on page 7)

Printing date 26.06.2008 Revision: 26.06.2008

Trade name: ProXL - Pro2kPrime

(Contd. of page 6)

Buildup of explosive mixtures possible without sufficient ventilation.

- · National regulations:
- $\cdot \textit{Waterhazard class:} \textit{Water hazard class 1 (Self-assessment): slightly hazardous for water.}$

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

- 10 Flammable.
- 11 Highly flammable.
- 12 Extremely flammable.
- 20/21 Harmful by inhalation and in contact with skin.
- 20/22 Harmful by inhalation and if swallowed.
- 36 Irritating to eyes.
- 37/38 Irritating to respiratory system and skin.
- 38 Irritating to skin.
- 41 Risk of serious damage to eyes.
- 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.
- · Contact: Anwendungstechnik
- * * Data compared to the previous version altered.

CD