

PRO2kPrime

Product Description

Pro2kPrime can be applied to a wide range of substrates with outstanding adhesion and filling quality's. It is very quick drying and isocyanate free.



Product Features

- Genuine two pack technology
- In-can activator system
- Non-isocyanate
- Long pot life
- Very good adhesion to bare sheet steel, zinc-coated steel and aluminium
- Outstanding build
- Fast air-drying time
- Easy, time-saving application

Usage

- Spot repair
- Refinishing of parts

Pre Treatment

The surface must be clean, dry and dust-free

Application

Mixing of ProXL 2K Prime with activator:



Remove cap from the bottom of the can. Remove the ring and feed through the hole in the bolt.



Shake the can for 2 minutes to ensure that the activator is completely mixed with the primer.



Pull the bolt in the bottom of the can with the aid of the metal ring as far as it will go.



After use, clear the valve by turning the aerosol upside down, pressing the nozzle for approx. 5 seconds.



By twisting 360°, the activator will be completely released

Pot life: approx. 24 hours.

Product Properties



2-3 spray passes, 60µ



After drying, wet sanding with P800-P1000

OR



Very rapid drying, after 40 min @ 70°F (20°C) or 30 min @ 140-160°F (60°C) or after 20 min. air-drying wet-on-wet re-coating



After drying, dry sanding with P400-P500



Infra-red drying 15-20 min.