## SAFETY DATA SHEET

Page 1 of 4

## **H20 GUN CLEANER**

Revision 5

Revision date 4-Jul-2007

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name H20 GUN CLEANER

Company Pro-Spray Automotive Finishes Ltd

Whitehall Industrial Estate

Cambridge Road

Croxton St Neots PE19 6SS

Catherine@pro-spray.co.uk

**Telephone** +44 (0) 1480 880035

Fax +44 (0) 1480 880108

Product code HGC-120

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

### Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Isopropanol	1-10%	67-63-0	200-661-7	F; R11 Xi; R36 R67
(Propan-2-ol)				
Ethylene glycol monobutyl ether	1-10%	111-76-2	203-905-0	Xn; R20/21/22 Xi; R36/38
(2-Butoxyethanol)				

### 3. HAZARDS IDENTIFICATION

Main hazards No Significant Hazard

## 4. FIRST AID MEASURES

**Skin contact** May cause irritation to skin. Remove contaminated clothing. Wash off immediately with

plenty of soap and water. Do NOT use solvents or thinners..

Eye contact May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes

holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation Move the exposed person to fresh air. Keep the affected person warm and at rest. If

unconscious, check for breathing and apply artificial respiration if necessary. If

breathing stops, provide artificial respiration. Seek medical attention.

Ingestion DO NOT INDUCE VOMITING. Keep the affected person warm and at rest. Seek

medical attention.

General information In case of accident or if you feel unwell, seek medical advice immediately (show the

label where possible).

Print date 8-Aug-2007

# **H20 GUN CLEANER**

Revision 5

Revision date 4-Jul-2007

### 5. FIRE FIGHTING MEASURES

Extinguishing media Carbon dioxide (CO2) Dry chemical. Use extinguishing media appropriate to the

surrounding fire conditions. Do NOT use water jet.

Fire hazards Fire will produce dense black smoke. Do not allow runoff water to enter sewers or

drains. Wear self contained breathing apparatus and protective clothing.

Protective equipment Self-contained breathing apparatus. Wear suitable respiratory equipment when

necessary.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions Eliminate all sources of ignition. Ensure adequate ventilation of the working area.

Evacuate personnel to a safe area. Wear suitable protective equipment.

Environmental precautions Advise local authorities if large spills cannot be contained. Do not allow product to enter

drains. Prevent further spillage if safe.

Clean up methods Absorb with inert, absorbent material. Clean area thoroughly with detergent. Transfer to

suitable, labelled containers for disposal.

#### 7. HANDLING AND STORAGE

Handling Ensure adequate ventilation of the working area. Keep away from sources of ignition -

No smoking. Adopt best Manual Handling considerations when handling, carrying and

dispensing

Storage Keep container tightly closed and in a well-ventilated place. Keep in a cool, dry, well

ventilated area. Store in correctly labelled containers. Store at temperatures between 5

°C and 35 °C.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## **Exposure limits**

 Isopropanol
 WEL 8-hr limit ppm: 400
 WEL 8-hr limit mg/m3: 999

 (Propan-2-ol)
 WEL 15 min limit ppm: 500
 WEL 15 min limit mg/m3: 1250

Ethylene glycol monobutyl ether WEL 8-hr limit ppm: 25 WEL 8-hr limit mg/m3: - (2-Butoxyethanol) WEL 15 min limit ppm: 50 WEL 15 min limit mg/m3: -

Ensure adequate ventilation of the working area.

Occupational exposure Isopropanol CAS#67-63-0 ACGIH TLV: 200 PPM OSHA STEL: 400PPM.

controls 2-Butoxyethanol CAS#111-76-2 ACGIH TLV: 20 PPM OSHA PEL: 50 PPM.

**Respiratory protection** Wear suitable respiratory equipment when necessary.

Hand protectionApply a barrier cream before handling the product. Nitrile rubber gloves.Eye protectionAvoid contact with eyes. In case of splashing, wear: Safety glasses.

Protective equipment Wear suitable protective equipment.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

DescriptionLiquid.Flash pointN/A°CRelative density0.995

Water solubility slightly miscible in water.

VOC (Volatile organic 41 g/l

compounds)

### 10. STABILITY AND REACTIVITY

Stability Stable under normal conditions.

# **H20 GUN CLEANER**

Revision 5

Revision date 4-Jul-2007

11. TOXICOLOGICAL INFORMATION

**Toxicological information**No data is available on this product.

12. ECOLOGICAL INFORMATION

Ecotoxicity No data is available on this product. Do not allow runoff water to enter sewers or drains.

13. DISPOSAL CONSIDERATIONS

General information Do not allow product to enter drains. Dispose of in compliance with all local and national

regulations.

Disposal of packaging Containers must be recycled in compliance with national legislation and environmental

regulations.

## 14. TRANSPORT INFORMATION

ADR/RID

UN 1263 Packing group III

Class 3 Hazard ID 33

Proper Shipping PAINT RELATED MATERIAL .

Name

**IMDG** 

UN 1263 Packing group III Class 3 Marine pollutant .

EmS Code F-E S-E

IATA

UN 1263 Packing group III
Class 3 Subsidiary risk -

Packing Instruction 310 Maximum quantity 220 L

(Cargo)

Packing Instruction 309 Maximum quantity 60 L

(Passenger)

**Further information** The product is not classifed as dangerous for carriage.

## 15. REGULATORY INFORMATION

Risk phrases NSH - No Significant Hazard.

Further information The information supplied in this Safety Data Sheet is designed only as guidance for the

safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other

process.

# **H20 GUN CLEANER**

Revision 5

Revision date 4-Jul-2007

## 16. OTHER INFORMATION

Text of risk phrases in R11 - Highly flammable.

Section 2 R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.

R36 - Irritating to eyes.

R36/38 - Irritating to eyes and skin.

R67 - Vapours may cause drowsiness and dizziness.

Further information The information supplied in this Safety Data Sheet is designed only as guidance for the

safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other

process.

**Revision** This document differs from the previous version in the following areas:

8 - occupational exposure controls.

Maximum content of VOC 41 g/l

Print date