SAFETY DATA SHEET

H20 PINK

Page 1 of 3

				Revision Revision date	3 4-Jul-2007
1. IDENTIFICATION OF THE SUBS	STANCE / PREPARATION AND THE C	OMPANY			100.2001
Product name	H20 PINK				
Company	Pro-Spray Automotive Finishes Ltd Whitehall Industrial Estate Cambridge Road Croxton St Neots PE19 6SS Catherine@pro-spray.co.uk				
Telephone	+44 (0) 1480 880035				
Fax	+44 (0) 1480 880108				
Product code	HST-511				
2. COMPOSITION / INFORMATION	N ON INGREDIENTS				
Hazardous ingredients					
	Conc.	CAS	EINECS	Symbols/Risk phrases	
Ethylene glycol monobutyl ether (2-Butoxyethanol)	1-10%	111-76-2	203-905-0	Xn; R20/21/22 Xi; R36/38	
2-Dimethylaminoethanol	0-0.5%	108-01-0	203-542-8	R10 Xn; R20/21/22 C; R34	
3. HAZARDS IDENTIFICATION					
Main hazards					
4. FIRST AID MEASURES					
Skin contact	-	May cause irritation to skin. Remove contaminated clothing. Wash off immediately with plenty of soap and water. Do NOT use solvents or thinners			
Eye contact		May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.			
Inhalation	Move the exposed person to fresh air. Keep the affected person warm and at rest. If unconscious, check for breathing and apply artificial respiration if necessary. If breathing stops, provide artificial respiration. Seek medical attention.				
Ingestion	DO NOT INDUCE VOMITING. Keep the affected person warm and at rest. Seek medical attention.				
General information	In case of accident or if you feel un label where possible).	well, seek medical	advice immediatel	y (show the	
5. FIRE FIGHTING MEASURES					
Extinguishing media	Carbon dioxide (CO2) Dry chemica surrounding fire conditions. Do NO	-	g media appropriat	e to the	
Fire hazards		Fire will produce dense black smoke. Do not allow runoff water to enter sewers or drains. Wear self contained breathing apparatus and protective clothing.			
Protective equipment	Self-contained breathing apparatus. Wear suitable respiratory equipment when necessary.				

H20 PINK

	Re	evision	3
	Revisio	on date	4-Jul-2007
6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	Eliminate all sources of ignition. Ensure adequate ventilation of the working area.		
	Evacuate personnel to a safe area. Wear suitable protective equipment.		
Environmental precautions	Advise local authorities if large spills cannot be contained. Do not allow product to enter		
	drains. Prevent further spillage if safe.		
Clean up methods	Absorb with inert, absorbent material. Clean area thoroughly with detergent. Transfer to		
	suitable, labelled containers for disposal.		
7. HANDLING AND STORAGE			
Handling	Ensure adequate ventilation of the working area. Keep away from sources of ignition -		

	No smoking. Adopt best Manual Handling considerations when handling, carrying and
	dispensing.
Storage	Keep container tightly closed and in a well-ventilated place. Keep in a cool, dry, well
	ventilated area. Store in correctly labelled containers. Store at temperatures between 5
	°C and 35 °C.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Ethylene glycol monobutyl ether	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m3: -
(2-Butoxyethanol)	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m3: -
2-Dimethylaminoethanol	WEL 8-hr limit ppm: 2	WEL 8-hr limit mg/m3: 7.4
	WEL 15 min limit ppm: 6	WEL 15 min limit mg/m3: 22
Engineering measures	Ensure adequate ventilation of the working area.	
Occupational exposure	2-Butoxyethanol CAS#111-76-2 ACGIH TLV: 20 PPM OSHA PEL: 50 PPM.	
controls		
Respiratory protection	Wear suitable respiratory equipment when necessary.	
Hand protection	Apply a barrier cream before handling the product. Nitrile rubber gloves.	
Eye protection	Avoid contact with eyes. In case of splashing, wear: Safety glasses.	
Protective equipment	Wear suitable protective equipment.	

9. PHYSICAL AND CHEMICAL PROPERTIES

9. FITTSICAL AND CHEMICAL PROPERTIES		
Description	Liquid.	
Flash point	N/A°C	
Relative density	1.015	
Water solubility	slightly miscible in water.	
VOC (Volatile organic compounds)	325 g/l	

10. STABILITY AND REACTIVITY

Stability		Stable under normal conditions.	
	11. TOXICOLOGICAL INFORMATION	I	

Toxicological information No data is available on this product. **12. ECOLOGICAL INFORMATION**

Ecotoxicity

No data is available on this product. Do not allow runoff water to enter sewers or drains.

H20 PINK

		Revision Revision date	3 4-Jul-2007
13. DISPOSAL CONSIDERATIONS			
General information	Do not allow product to enter drains. Dispose of in compliance with all local and nation regulations.	nal	
Disposal of packaging	Containers must be recycled in compliance with national legislation and environmenta regulations.	I	
14. TRANSPORT INFORMATION			
Further information	The product is not classifed as dangerous for carriage.		
15. REGULATORY INFORMATION			
Symbols	Xi - Irritant		
	A i		
Risk phrases	R36/38 - Irritating to eyes and skin.		
	R43 - May cause sensitisation by skin contact.		
Safety phrases	S24 - Avoid contact with skin.		
	S37 - Wear suitable gloves.		
Further information	The information supplied in this Safety Data Sheet is designed only as guidance for the	ie	
	safe use, storage and handling of the product. This information is correct to the best of	of	
	our knowledge and belief at the date of publication however no guarantee is made to		
	accuracy. This information relates only to the specific material designated and may no		
	be valid for such material used in combination with any other materials or in any other process.		
16. OTHER INFORMATION			
Text of risk phrases in	R10 - Flammable.		
Section 2	R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.		
	R34 - Causes burns.		
	R36/38 - Irritating to eyes and skin.		
Further information	The information supplied in this Safety Data Sheet is designed only as guidance for th	ie	
	safe use, storage and handling of the product. This information is correct to the best of	of	
	our knowledge and belief at the date of publication however no guarantee is made to	its	
	accuracy. This information relates only to the specific material designated and may no	ot	
	be valid for such material used in combination with any other materials or in any other process.		
Revision	This document differs from the previous version in the following areas:		
	8 - occupational exposure controls.		
Maximum content of VOC	325 g/l		