SAFETY DATA SHEET

H20 GALAXY BLUE

Page 1 of 3

				Revision	4		
				Revision date	، 5-Jul-2007		
1. IDENTIFICATION OF THE SU	BSTANCE / PREPARATION AND THE	COMPANY					
Product name	H20 GALAXY BLUE						
Company	Pro-Spray Automotive Finishes L Whitehall Industrial Estate Cambridge Road Croxton St Neots PE19 6SS Catherine@pro-spray.co.uk	td					
Telephone	+44 (0) 1480 880035						
Fax	+44 (0) 1480 880108						
Product code	XCT-104						
2. COMPOSITION / INFORMATI	ON ON INGREDIENTS						
Hazardous ingredients							
	Conc.	CAS	EINECS	Symbols/Risk phrases			
Ethylene glycol monobutyl ether (2-Butoxyethanol)	1-10%	111-76-2	203-905-0	Xn; R20/21/22 Xi; R36/38			
2-Dimethylaminoethanol	0-0.5%	108-01-0	203-542-8	R10 Xn; R20/21/22 C; R34			
3. HAZARDS IDENTIFICATION							
Main hazards	Irritating to eyes and skin. May ca	ause sensitisation by	v skin contact.				
4. FIRST AID MEASURES							
Skin contact	May cause irritation to skin. Remove contaminated clothing. Wash off immediately with plenty of soap and water. Do NOT use solvents or thinners						
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes						
	holding the eyelids open. Seek medical attention if irritation or symptoms persist.						
Inhalation	Move the exposed person to fresh air. Keep the affected person warm and at rest. If						
	unconscious, check for breathing and apply artificial respiration if necessary. If breathing stops, provide artificial respiration. Seek medical attention.						
Ingestion	DO NOT INDUCE VOMITING. K			st Seek			
	medical attention.						
General information	In case of accident or if you feel u	unwell, seek medica	l advice immediatel	y (show the			
	label where possible).						
5. FIRE FIGHTING MEASURES							
Extinguishing media	Carbon dioxide (CO2) Dry chemi surrounding fire conditions. Do N	-	ng media appropria	te to the			
Fire hazards	Fire will produce dense black smoke. Do not allow runoff water to enter sewers or						
	drains. Wear self contained breat						
Protective equipment	Self-contained breathing apparat	us. Wear suitable re	spiratory equipmen	t when			

necessary.

Page 2 of 3

H20 GALAXY BLUE

		Revision Revision date	4 5-Jul-2007		
6. ACCIDENTAL RELEASE MEASU	IRES	Revision date	5-301-2007		
Personal precautions	Eliminate all sources of ignition. Ensure adequate ventilation of the	working area.			
	Evacuate personnel to a safe area. Wear suitable protective equipment.				
Environmental precautions	Advise local authorities if large spills cannot be contained. Do not allow product to enter drains. Prevent further spillage if safe.				
Clean up methods	Absorb with inert, absorbent material. Clean area thoroughly with detergent. Transfer to				
	suitable, labelled containers for disposal.				
7. HANDLING AND STORAGE		7 . 10			
Handling	Ensure adequate ventilation of the working area. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing.				
Storage	Keep container tightly closed and in a well-ventilated place. Keep in a cool, dry, well ventilated area. Store in correctly labelled containers. Store at temperatures between 5 °C and 35 °C.				
8. EXPOSURE CONTROLS / PERS	ONAL PROTECTION				
Exposure limits					
Ethylene glycol monobutyl ether (2-Butoxyethanol)	WEL 8-hr limit ppm: 25 WEL 15 min limit ppm: 50	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: -			
2-Dimethylaminoethanol	WEL 8-hr limit ppm: 2 WEL 15 min limit ppm: 6	WEL 8-hr limit mg/m3: 7.4 WEL 15 min limit mg/m3: 22			
Engineering measures	Ensure adequate ventilation of the working area.				
Occupational exposure controls	2-Butoxyethanol CAS#111-76-2 ACGIH TLV: 20 PPM OSHA PEL: 50 PPM. Aluminium CAS# 7429-90-5 ACGIH TLV: 10mg/m3 OSHA PEL: 15mg/m3 Respirable 5 mg/m3 Titanium Dioxide CAS# 13463-67-7 ACGIH TLV: 10mg/m3 OSHA PEL: 15mg/m3				
Respiratory protection	Wear suitable respiratory equipment when necessary.				
Hand protection	Apply a barrier cream before handling the product. Nitrile rubber gloves.				
Eye protection	Avoid contact with eyes. In case of splashing, wear: Safety glasses.				
Protective equipment	Wear suitable protective equipment.				
9. PHYSICAL AND CHEMICAL PRO	PERTIES				
Description	Liquid.				
Relative density	1.092				
Water solubility	slightly miscible in water.				
VOC (Volatile organic compounds)	327 g/l				
10. STABILITY AND REACTIVITY					

11. TOXICOLOGICAL INFORMATION

Toxicological information No data is available on this product. 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data is available on this product. Do not allow runoff water to enter sewers or drains.

H20 GALAXY BLUE

		Revision	5 14 000
13. DISPOSAL CONSIDERATIO	NS	Revision date	5-Jul-200
General information	Do not allow product to enter drains. Dispose of in compliance with all local and natio	nal	
	regulations.		
Disposal of packaging	Containers must be recycled in compliance with national legislation and environmenta	al	
	regulations.		
14. TRANSPORT INFORMATIO	N		
Further information	The product is not classifed as dangerous for carriage.		
15. REGULATORY INFORMATI	ON		
Symbols	Xi - Irritant		
	A i		
Risk phrases	R36/38 - Irritating to eyes and skin.		
	R43 - May cause sensitisation by skin contact.		
Safety phrases	S24 - Avoid contact with skin.		
	S37 - Wear suitable gloves.		
Further information	The information supplied in this Safety Data Sheet is designed only as guidance for the	ne	
	safe use, storage and handling of the product. This information is correct to the best of	of	
	our knowledge and belief at the date of publication however no guarantee is made to	its	
	accuracy. This information relates only to the specific material designated and may no	ot	
	be valid for such material used in combination with any other materials or in any other	r	
	process.		
16. OTHER INFORMATION			
Text of risk phrases in	R10 - Flammable.		
Section 2	R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.		
	R34 - Causes burns.		
	R36/38 - Irritating to eyes and skin.		
Further information	The information supplied in this Safety Data Sheet is designed only as guidance for the	ne	
	safe use, storage and handling of the product. This information is correct to the best of	of	
	our knowledge and belief at the date of publication however no guarantee is made to	its	
	accuracy. This information relates only to the specific material designated and may no	ot	
	be valid for such material used in combination with any other materials or in any other		
	process.		
Revision	This document differs from the previous version in the following areas:		
	8 - occupational exposure controls.		
Maximum content of VOC	327 g/l		
	-		